



# V A L V E S

## In-Line Flow Control Valves



### FEATURES:

- Carbon steel body
- Designed to provide precision flow control & shut off in one flow direction & provide free flow in the opposite direction
- Color bands allow fast return to a previous setting
- Set screw locks valve to any setting
- Operating temp range -20°F through 210°F

## Model In-Line Flow Control Valves

MODEL No.	PORT SIZE	MAX PSI	MAX FLOW	SHIPPING WEIGHT	LIST PRICE
WFC-400	1/4" NPTF	5,000 PSI	5 GPM	0.5	37.60
WFC-600	3/8" NPTF	5,000 PSI	8 GPM	0.9	40.40
WFC-800	1/2" NPTF	5,000 PSI	15 GPM	1.5	50.10
WFC-1200	3/4" NPTF	3,000 PSI	25 GPM	2.5	97.30
WFC-1600	1" NPTF	3,000 PSI	40 GPM	3.5	236.60

MODEL NO.	MAX FLOW	A	B	C	D	E	F	G	H
WFC-400	5 GPM	1/4 NPTF	1.79	1.59	2.62	1.66	.81	.41	.811
WFC-600	8 GPM	3/8 NPTF	2.18	1.94	2.75	1.75	1	.5	1
WFC-800	15 GPM	1/2 NPTF	2.70	2.42	3.44	2.23	1.25	.63	1.19
WFC-1200	25 GPM	3/4 NPTF	3.38	2.81	3.88	2.58	1.5	.75	1.38
WFC-1600	40 GPM	1 NPTF	4.87	4.21	5	3.22	1.75	.88	1.88

