



V A L V E S

In-Line Needle Valves



FEATURES:

- Carbon steel body
- Designed to provide precision flow control
- Operating temp range -20°F through 210°F

Model In-Line Needle Valves

MODEL No.	PORT SIZE	MAX PSI	MAX FLOW	SHIPPING WEIGHT	LIST PRICE
WNV-400	1/4" NPTF	5,000 PSI	5 GPM	0.6	30.29
WNV-600	3/8" NPTF	5,000 PSI	8 GPM	1.0	40.82
WNV-800	1/2" NPTF	5,000 PSI	16 GPM	1.8	51.36
WNV-1200	3/4" NPTF	3,000 PSI	25 GPM	3.0	92.20
WNV-1600	1" NPTF	3,000 PSI	40 GPM	4.2	223.91

MODEL NO.	MAX FLOW	MAX PSI	A	B	C	D	E	F
WNV-400	5 GPM	5000	1/4 NPTF	2.6	0.75	2	2	M18-1.8
WNV-600	8 GPM	5000	3/8 NPTF	4.2	1	2.5	2.5	M22-1.5
WNV-800	16 GPM	5000	1/2 NPTF	5.1	1.25	2.62	3.25	M28-1.5
WNV-1200	25 GPM	3000	3/4 NPTF	5.6	1.5	3.25	3.88	M33-1.5
WNV-1600	40 GPM	3000	1 NPTF	5.8	1.75	4.25	3.88	M35-2.0

